



(11) **EP 1 168 817 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
02.01.2002 Bulletin 2002/01

(51) Int Cl.7: **H04N 1/32**

(21) Application number: 01305333.5

(22) Date of filing: 19.06.2001

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
 MC NL PT SE TR**
 Designated Extension States:
AL LT LV MK RO SI

- Tsumori, Shinichi
Kadoma-shi, Osaka 571-8501 (JP)
- Shimizu, Yuji
Kadoma-shi, Osaka 571-8501 (JP)
- Katsura, Takashi
Kadoma-shi, Osaka 571-8501 (JP)
- Inoue, Hisashi
Kadoma-shi, Osaka 571-8501 (JP)

(30) Priority: 20.06.2000 JP 2000184866

(71) Applicant: **MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.**
Kadoma-shi, Osaka 571-8501 (JP)


**(74) Representative: Shelley, Mark Raymond et al
K R Bryer & Co., 7 Gay Street
Bath BA1 2PH (GB)**

(72) Inventors:
• **Kawaguchi, Yuichi**
Kadoma-shi, Osaka 571-8501 (JP)

(54) **Authenticating system, personal certification issuing system, personal certificate and methods therefor**

(57) A justification/authentication personal certificate system stores in a remote database (3) a counterpart of an identifier (11) and a digital watermark contained in the personal certificate (10). The personal certificate includes the digital watermark embedded in an authentic image (12) such as a facial photograph, a retinal scan, or a fingerprint. When the personal certificate is used, the authentic image is read from the personal certificate, and the digital watermark information is extracted. The digital watermark information and the identifier are compared with the counterparts stored in the database. If the extracted digital watermark information is identical to the information in the database, then the personal certificate is judged to be unjustifiable. In one embodiment, at least one of the identifier and digital watermark are changed each time the system justifies the personal certificate.

Fig. 1



Description

[0001] This invention relates to a justification authenticating system, a personal certificate issuing system, and a personal certificate used in these systems. The invention also concerns a method for issuing personal certificates and a method for authenticating personal certificates.

[0002] In general, personal certificates that include authentic images (of a card type or a book type), such as a credit card, cash card, membership card, student identification card, employee ID card, passport, health insurance card, and license, have been widely used. In this specification, the "authentic image" signifies an image by which an individual is identified, such as a photographic image of a face, an image of a fingerprint, or an image of a pupil or iris.

[0003] Incidents frequently occur in which a person who is not the rightful owner of a personal certificate substitutes an authentic image of the owner for another authentic image to impersonate the rightful owner. This is a social problem.

[0004] As a countermeasure against such counterfeiting, a technique for embedding a digital watermark into a facial photograph has been proposed (see Japanese Unexamined Patent Publication No. Hei-10-275203), the disclosure of which is herein included by reference.

[0005] According to the digital watermark method, digital data is embedded into an authentic image as a watermark so as to be indistinguishable to the eye, while permitting normal viewing of the authentic image.

[0006] In this technique, the justification of a personal certificate is judged in such a way that a digital watermark embedded in the personal certificate is accurately extracted by the aid of authentication equipment (for example, a card reader).

[0007] In one method, when a personal certificate is formed, an identifier of the owner of the certificate may be "BBB", for example, information to be added may be "AAA", and the digital watermark of "ABABAB" is created and embedded.

[0008] In this case, the digital watermark is read from an authentic image when authenticated. If the reading fails, the identification is judged to be unjustifiable. If the reading is successful, according to an opposite procedure to the procedure followed when embedded, the identifier "BBB" is extracted from the digital watermark "ABABAB", and the information "AAA" is extracted. A judgment is then made as to whether or not the information is correct. If the information is correct, it is judged to be justifiable, and, if not, it is judged to be unjustifiable.

[0009] A disadvantage of the above technique is that, since the justification is determined only by the data stored on the card, falsification is easily perpetrated if the algorithm for embedding the digital watermark is leaked or revealed. For example, the illegality of an offender B will not be exposed if the offender, who stole the credit card of a person A, merely pastes a facial pho-

tograph of the offender on it in which a digital watermark according to the known algorithm is embedded in it, and the offender B uses this altered credit card. Accordingly, the above technique cannot completely avoid security problems.

[0010] Briefly stated, an aspect of the present invention provides a justification/authentication personal certificate system which stores in a remote database a counterpart of an identifier and a digital watermark contained in the personal certificate. The personal certificate includes the digital watermark embedded in an authentic image such as a facial photograph, a retinal scan, or a fingerprint. When the personal certificate is used, the authentic image is read from the personal certificate, and the digital watermark information is extracted. The digital watermark information and the identifier are compared with the counterparts stored in the database. If the extracted digital watermark information is identical to the information in the database, then the personal certificate is judged to be unjustifiable. In one embodiment, at least one of the identifier and digital watermark are changed each time the system justifies the personal certificate.

[0011] According to an aspect of the invention, there is provided a justification authenticating system comprising: a database for storing an identifier of a personal certificate and digital watermark information related to said identifier, a personal certificate containing said identifier, said personal certificate also containing a readable authentic image in which a digital watermark relative to said identifier is embedded, a read means for reading at least said authentic image from said personal certificate, a watermark information inquiring means for extracting digital watermark information corresponding to said identifier from said authentic image, and a watermark information comparing means for judging whether said digital watermark information extracted by said watermark information inquiring means from said personal certificate is identical to said watermark information stored in said database, if said watermark inquiring means finds identical watermark information in said watermark information from said authentic image and said database, said watermark inquiring means justifies said personal certificate, and if the watermark information from the two sources are not identical, then the watermark inquiring means fails to justify said personal certificate.

[0012] According to another aspect of the invention, there is provided a personal certificate issuing system comprising: an identifier generating means for generating an identifier unique to a personal certificate, a watermark information generating means for generating digital watermark information corresponding to said identifier, a database for storing said identifier of said personal certificate and said digital watermark information relative to said identifier in relation to each other, a watermark information registering means for storing said identifier generated by said identifier generating

means and said digital watermark information generated by said watermark information generating means in said database, an image input means for inputting a raw authentic image, a watermark-embedded image forming means for forming a watermark-embedded authentic image in which said digital watermark is embedded on said authentic image input by said image input means, and a personal certificate that readably carries said authentic image generated by said watermark-embedded image forming means and said identifier generated by said identifier generating means.

[0013] According to a further aspect of the invention, there is provided a personal certificate comprising: a unique identifier, an authentic image of an authorized user of said personal certificate, said authentic image being viewable by eye, said authentic image containing embedded therein digital watermark information corresponding to said identifier, and means for permitting communication of said identifier and said digital watermark information to a database remote from said personal certificate.

[0014] Preferably, digital watermark information embedded in an authentic image is stored not only on the authentic image of a personal certificate but also on a database, and therefore only justifiable use is permitted following a comparison of the digital watermark information stored in the database and the digital watermark information extracted from the personal certificate.

[0015] For example, since the database itself is not modified even if digital watermark information is embedded expertly in the facial photograph of a personal certificate stolen by the offender B, the comparison with the database fails, and the illegality of the offender B is exposed, that is to say, compared with the case in which security depends only on the authentic image of the personal certificate, security can be greatly improved.

[0016] Preferably, the digital watermark stored in the information carrier can be read as digital data, and therefore the digital watermark information can be accurately compared.

[0017] Preferably, the information carrier is a semiconductor memory or a magnetic material, and therefore data can be stored without greatly increasing the weight of the personal certificate.

[0018] Preferably, the authentic image is printed on printed matter, and therefore the personal certificate is thinner and lighter.

[0019] Preferably, random values are included in the digital watermark information. Therefore, persons who attempt falsification or alteration cannot predict the random portion of the information. This increases the difficulty of falsification.

[0020] Preferably, the digital watermark information embedded in the facial photograph information of the database and of the personal certificate is updated whenever necessary or desirable. Therefore, infallible measures can be taken against falsification.

[0021] Preferably, the database is located at a dis-

tance from the place where the personal certificate is used. The data is communicated through a communication network. Thus, the digital watermark information does not leak out as long as access to the database is prevented. Therefore, the security of the system is improved.

[0022] Various embodiments of the invention will now be more particularly described, by way of example, with reference to the accompanying drawings, in which:

Fig. 1 is a block diagram of a system according to a first embodiment of the present invention.

Fig. 2 is a block diagram of a system according to a second embodiment of the present invention.

Fig. 3 is a flowchart showing an issuing process according to the first embodiment of the present invention.

Fig. 4 is a flowchart showing an authentication process of the present invention.

Fig. 5 schematically shows the relationship among a personal certificate, an identifier, a digital watermark, and a database of the same.

[0023] Embodiments of the present invention are described hereinafter with reference to the accompanying drawings. First, prior to the description of each embodiment, the relationship among an identifier, digital watermark information, and a database according to the present invention is roughly described with reference to Fig. 5. A case where the photographic image of a face is used as an authentic image is primarily described below.

[0024] As shown in Fig. 5, a personal certificate 5 includes an identifier 1 and an authentic image 4. There is a one-to-one relationship between the identifier 1 and digital watermark information 2 which are stored in a database 3. In this example, for purposes of description, and not as a limitation, the identifier 1 is "123", and the digital watermark information 2 is "hogehege".

[0025] Referring to Fig. 1, a system according to the first embodiment of the present invention employs a personal certificate 10 shown at the upper left of Fig. 1. The personal certificate 10 is one that has been issued, and is used for authentication. A personal certificate 20 shown at the upper right of Fig. 1 is being prepared for issue, but has not yet been completed for issue.

[0026] The completed and issued personal certificate 10 has a display part 12 in which a photograph of a face or the like is displayed, a memory 13 as an information carrier, and an identifier 11 (in this embodiment, "123").

[0027] The personal certificate 10 further has an input-output port 14 to access the memory 13. If the capacity is large enough to store an image, a magnetic material, such as a magnetic strip, may be used as an

information carrier instead of the memory 13.

[0028] An authentic image in which digital watermark information is embedded, is stored in the memory 13. The authentic image can be displayed on the display part 12 if necessary. The display part 12 may be, for example, an LCD.

[0029] Likewise, the personal certificate 20 being prepared for issue includes an identifier 21 (herein "234"), a display part 22, a memory 23, and an input-output port 24. The personal certificate is constructed in this way.

[0030] Next, a system of this embodiment is described. For convenience of explanation, this system is a combination of a justification authenticating system and a personal certificate issuing system. However, the authenticating system and the issuing system can be separately constructed.

[0031] A reading means 30 is connected to the input-output port 14. The connection of the reading means 30 may be a wired or wireless connection. The reading means 30 reads the authentic image that is stored in the memory 13 and in which digital watermark information is embedded.

[0032] A write means 31 is connected to the input-output port 24. The connection of the write means 31 may be a wired or wireless connection. The write means 31 writes into the memory 23 facial photograph information in which digital watermark information is embedded.

[0033] An input means 32 accepts information input needed when a personal certificate is authenticated or issued. A digital camera 33 photographs the face of an owner, and outputs an authentic image (digital) of the face photographed. A control means 34 controls the above, and other elements, and judges the verification of the personal certificate.

[0034] A watermark information extracting means 35 extracts only the digital watermark information from the authentic image read by the reading means 30, and returns the digital watermark information to the control means 34.

[0035] A watermark information comparing means 36 compares the watermark information obtained from the database 3 with the watermark information extracted by the watermark information extracting means 35, and returns a judgment to the control means 34 on whether or not the two sources of watermark information are identical.

[0036] As described later, a watermark-embedded image forming means 37 embeds generated watermark information obtained from a server 42 side into the authentic image photographed by the digital camera 33, and forms an authentic image in which a digital watermark is embedded.

[0037] A watermark information registering means 38 requests the server 42 to register an identifier and a digital watermark corresponding to the identifier on the database 3. A watermark information inquiring means 39 sends the identifier to the database 3 through the server 42, and requests watermark information relative to the

identifier. A communication means 40 communicates with the server 42 through a communication network 41.

[0038] The server 42 is connected to an identifier generating means 43 and a watermark information generating means 44. The identifier generating means 43 accesses the database 3, and generates a unique identifier that has not yet been assigned. The watermark information generating means 44 forms watermark information corresponding to the identifier.

[0039] The watermark information is preferably determined arbitrarily. Preferably, the watermark information is based on a random number generator (pseudo-random number generator). With watermark information generated according to random numbers, persons (offenders or their group) who attempt falsification, cannot predict the information in a new watermark based on knowledge of preceding watermarks. This provides an additional level of security for the system. Typically, the watermark information is recorded on the database 3 as text data, and is embedded into the authentic image as a digital watermark.

[0040] Although the authentic image is obtained by photography using the digital camera 33 in the example of Fig. 1, the authentic image may be input by any convenient input device such as, for example, reading in printed matter with an image scanner or the like. If a fingerprint image or a pupil image, instead of a face image, is employed as the authentic image, an input means suitable for such an image is used, as a matter of course.

[0041] The identifier generating means 43 and the watermark information generating means 44 may be disposed on the control means 34 side (i.e., the client side when seen from the server 42), instead of on the server 42 side.

[0042] Next, a system according to a second embodiment of the present invention is described with reference to Fig. 2. In this system, a personal certificate does not include a memory as an information carrier. This embodiment differs from that of Fig. 1 in the following respect.

[0043] Although an identifier 51 (herein "123") is displayed on a personal certificate 50 for authentication, an information carrier is omitted. Accordingly, an input-output port is not required. Instead of a memory and input-output port, a printed facial photograph 52 is pasted on the personal certificate 50. The printed facial photograph 52 is input through an image scanner 70.

[0044] Likewise, although an identifier 61 (herein "234") is displayed on a personal certificate 60 for issue, a memory and an input-output port are also omitted. Instead, a pasting area for a facial photograph 62 is available for pasting therein. Digital watermark information is embedded in the facial photograph 62. The facial photograph 62, together with the digital watermark information is printed on the personal certificate 60 by a printer 71. The resulting facial photograph 62 is pasted on the pasting area of the personal certificate 60. The remain-

ing aspects of the system are identical to the structure of Fig. 1.

[0045] Next, the flow of a process for issuing the personal certificate is described hereinafter with reference to Fig. 3. In the second embodiment, the technique of the reading/writing of the authentic image merely differs in the processing itself, and therefore the first embodiment is primarily described.

[0046] First, the operator of this system or the owner of the personal certificate inputs necessary personal information to the system using the input means 32 (step 1). Thereafter, at step 2, the owner's face, corneal pattern, fingerprint, or other identifying pattern, is photographed with the digital camera 33, scanner, or other device, to acquire an authentic image.

[0047] At step 3, the control means 34 connects to the server 42 through the communication network 41 using the communication means 40.

[0048] Thereafter, at step 4, the control means 34 requests the server 42 to generate an identifier and watermark information corresponding to this identifier through the communication means 40.

[0049] In response to this, the identifier generating means 43 on the server 42 side accesses the database 3, and generates a new identifier that has not yet been assigned. The watermark information generating means 44 generates watermark information corresponding to this new identifier. The identifier and the watermark information are transmitted to the control means 34 (step 5).

[0050] The control means 34 receives them, and requests the watermark information registering means 38 to register the received identifier and watermark information on the database 3 (step 6). In response to this demand, the server 42 stores the information in the database 3. Thereafter notification is transmitted to the control means 34 that the registration has been completed (step 7).

[0051] Upon receiving this notification, the control means 34 releases the connection with the server 42 (step 8), and gives the received watermark information and the authentic image obtained from the digital camera 33 to the watermark-embedded image forming means 37, and thereby a watermark-embedded image is formed (step 9).

[0052] At step 10, the watermark-embedded image formed as described above is transmitted to the write means 31. The write means 31 writes this image into the memory 23 through the input-output port 24, and the authentic image is displayed on the display part 22 when necessary. This completes the issuing process.

[0053] Next, the authentication process is described with reference to Fig. 4. The personal certificate 10 that has been issued is inserted into the read means 30. First, the read means 30 reads an identifier 11 (herein "123") from the personal certificate 10 (step 20). The identifier may be input by any convenient device such as, for example, with the input means 32.

[0054] Thereafter, at step 21, the read means 30 reads the authentic image that is stored in the memory 13 and in which digital watermark information is surely embedded, through the input-output port 14.

[0055] Thereafter, at step 22, the control means 34 transmits the obtained authentic image to the watermark information extracting means 35, and causes the extracting means 35 to extract watermark information from the authentic image. If this extraction fails (step 23), the control means 34 judges that the personal certificate 10 is unjustifiable (step 24), and terminates the processing.

[0056] On the other hand, if the extraction of the watermark information succeeds, the control means 34 connects to the server 42 through the communication means 40 (step 25).

[0057] The control means 34 transmits the identifier 11 that has been read from the personal certificate to the watermark information inquiring means 39, and causes the inquiring means 39 to acquire the watermark information corresponding to the identifier 11 (step 26).

[0058] When receiving this inquiry, the server 42 retrieves the watermark information corresponding to the identifier in the database 3. If the watermark information is not found, the server 42 sends a message that the corresponding information is not found. If the watermark information is found, the server 42 returns the found watermark information to the control means 34 (step 27).

[0059] When the control means 34 receives the information from the server 42, the control means 34 releases the connection (step 28). If the control means 34 receives the message that the watermark information is not found (step 29), it is judged that the personal certificate 10 is unjustifiable (step 24), and the processing is terminated.

[0060] On the other hand, when receiving the watermark information, the control means 34 transmits the watermark information extracted by the watermark information extracting means 35 and the watermark information received from the server 42 at this time to the watermark information comparing means 36 for a comparison. If the watermark information from the two sources are found to be non-identical in the comparison made by the watermark information comparing means 36, the control means 34 determines that the personal certificate 10 is unjustifiable (step 24), and terminates the processing.

[0061] On the other hand, if the watermark information from the two sources are found to be identical in the comparison, the control means 34 determines that the personal certificate 10 is justifiable (step 31), and completes the processing.

[0062] Preferably, when the watermark is judged to be justifiable, the same process as the main part of Fig. 3 is carried out once again at step 32, and the watermark information corresponding to this identifier is updated (step 32). As a matter of course, the update means updates both the digital watermark embedded in the authentic image of the personal certificate 10 and the dig-

ital watermark in the database 3 (note that these digital watermarks are caused to be identical). If so, the digital watermark is updated whenever the authentication process succeeds. This adds an additional defense against falsification or forgery.

[0063] As described above, in the present invention, the digital watermark embedded in the authentic image of the personal certificate does not depend only on proof by authentication equipment. Instead, it compares the digital watermark stored in the database remote from the personal certificate or the authentication equipment with the digital watermark with the digital watermark on the personal certificate. Therefore, a preventive system against falsification or against other unjustifiable use is constructed.

[0064] Having described preferred embodiments of the invention with reference to the accompanying drawings, it is to be understood that the invention is not limited to those precise embodiments, and that various changes and modifications may be effected therein by one skilled in the art without departing from the scope or spirit of the invention as defined in the appended claims.

Claims

1. A justification authenticating system comprising:

a database (3) for storing an identifier of a personal certificate and digital watermark information related to said identifier;
 a personal certificate (10) containing said identifier;
 said personal certificate also containing a readable authentic image (12) in which a digital watermark relative to said identifier is embedded;
 a read means (30) for reading at least said authentic image from said personal certificate;
 a watermark information inquiring means (39) for extracting digital watermark information corresponding to said identifier from said authentic image; and
 a watermark information comparing means (36) for judging whether said digital watermark information extracted by said watermark information inquiring means from said personal certificate is identical to said watermark information stored in said database;
 if said watermark inquiring means finds identical watermark information in said watermark information from said authentic image and said database, said watermark inquiring means justifies said personal certificate; and
 if the watermark information from the two sources are not identical, then the watermark inquiring means fails to justify said personal certificate.

2. The justification authenticating system of claim 1, wherein said personal certificate includes:

an information carrier (13) for storing said authentic image; and
 said digital watermark is embedded in said authentic image stored in said information carrier.

3. The justification authenticating system of claim 2, wherein said information carrier is at least one of a semiconductor memory and a magnetic recording material.

4. The justification authenticating system of claim 2, wherein:

said information carrier includes said authentic image being a printed authentic image (62) affixed to said personal certificate; and
 said read means reads said printed image.

5. The justification authenticating system of claim 1, wherein at least one of said identifier and said digital watermark information includes an element that is randomly generated.

6. The justification authenticating system of claims 1, further comprising:

means for updating said digital watermark information (38) stored in said database and said digital watermark information embedded in said authentic image in said personal certificate each time said watermark information inquiring means judges said digital watermark information to be justifiable.

7. The justification authenticating system of claim 1, further comprising:

a communication device (40, 41) for communicating said watermark information between said watermark information inquiring means and said database.

8. A personal certificate issuing system comprising:

an identifier generating means (43) for generating an identifier unique to a personal certificate;
 a watermark information generating means (44) for generating digital watermark information corresponding to said identifier;
 a database (3) for storing said identifier of said personal certificate and said digital watermark information relative to said identifier in relation to each other;
 a watermark information registering means

(38) for storing said identifier generated by said identifier generating means and said digital watermark information generated by said watermark information generating means in said database;

an image input means (32, 33) for inputting a raw authentic image;

a watermark-embedded image forming means (37) for forming a watermark-embedded authentic image in which said digital watermark is embedded on said authentic image input by said image input means; and

a personal certificate (10) that readably carries said authentic image generated by said watermark-embedded image forming means and said identifier generated by said identifier generating means.

9. The personal certificate issuing system of claim 8, wherein:

said personal certificate includes an information carrier (13) for storing said authentic image; and

said authentic image includes a digital watermark embedded in said authentic image stored in said information carrier.

10. The personal certificate issuing system of claim 9, wherein said information carrier is at least one of a semiconductor memory and a magnetic material.

11. The personal certificate issuing system of claim 9 wherein:

said information carrier includes said authentic image being a printed authentic image affixed to said personal certificate; and
said read means reads said printed authentic image.

12. The personal certificate issuing system of claim 8, wherein at least one of said identifier and said digital watermark information includes an element that is randomly generated.

13. The personal certificate issuing system of claim 8, wherein said digital watermark information stored in said database and embedded in said authentic image of said personal certificate are updated at a predetermined time.

14. The personal certificate issuing system of claim 13, wherein said predetermined time includes each time said system correctly justifies an authentic image.

15. The personal certificate issuing system of claim 8,

further comprising:

a communication device for communicating said watermark information between said watermark information inquiring means and said database.

16. A personal certificate (10) comprising:

a unique identifier (11);
an authentic image (12) of an authorized user of said personal certificate;
said authentic image being viewable by eye;
said authentic image containing embedded therein digital watermark information corresponding to said identifier; and
means for permitting communication (40, 41) of said identifier and said digital watermark information to a database (3) remote from said personal certificate.

17. A method for issuing a personal authentication certificate; the said method comprising the steps of:

generating an identifier (11) unique to a personal certificate (10);
generating data relating to a digital watermark for the said identifier;
storing data relating to the said identifier, digital watermark and personal certification in relation to each other;
inputting an image to be associated with the said personal certification;
processing the said image with the said watermark data to form a watermark-embedded authentication image (12) for the said personal certificate.

18. A method for authenticating a personal authentication certificate; the said method comprising the steps of:

reading at least an authentication image (12) from a personal authentication certificate (3);
processing the said authentication image (35) to extract data relating to watermark embedded in the said image;
comparing the said extracted embedded watermark data with watermark data stored in a data storage means (11) in relation to an identifier (11) for the said personal authentication certificate;
determining whether the said extracted embedded watermark data corresponds with the said stored watermark data (36), whereby to authenticate the personal authentication certificate.

19. A method according to Claim 18 further comprising the step of receiving the said stored data from a database connected to a remote personal certificate reading means via a communication network.

5

10

15

20

25

30

35

40

45

50

55

Fig. 1




Fig. 2




Fig. 3




Fig. 4





Fig. 5





(11)

EP 1 168 817 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
12.03.2003 Bulletin 2003/11

(51) Int Cl.7: **H04N 1/32**

(43) Date of publication A2:
02.01.2002 Bulletin 2002/01

(21) Application number: 01305333.5

(22) Date of filing: 19.06.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
 Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 20.06.2000 JP 2000184866

(71) Applicant: **MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.**
Kadoma-shi, Osaka 571-8501 (JP)

(72) Inventors:
• **Kawaguchi, Yuichi**
Kadoma-shi, Osaka 571-8501 (JP)


- Tsumori, Shinichi
Kadoma-shi, Osaka 571-8501 (JP)
- Shimizu, Yuji
Kadoma-shi, Osaka 571-8501 (JP)
- Katsura, Takashi
Kadoma-shi, Osaka 571-8501 (JP)
- Inoue, Hisashi
Kadoma-shi, Osaka 571-8501 (JP)

(74) Representative: **Shelley, Mark Raymond et al**
K R Bryer & Co.,
7 Gay Street
Bath BA1 2PH (GB)

(54) **Authenticating system, personal certification issuing system, personal certificate and methods therefor**

(57) A justification/authentication personal certificate system stores in a remote database (3) a counterpart of an identifier (11) and a digital watermark contained in the personal certificate (10). The personal certificate includes the digital watermark embedded in an authentic image (12) such as a facial photograph, a retinal scan, or a fingerprint. When the personal certificate is used, the authentic image is read from the personal certificate, and the digital watermark information is extracted. The digital watermark information and the identifier are compared with the counterparts stored in the database. If the extracted digital watermark information is identical to the information in the database, then the personal certificate is judged to be unjustifiable. In one embodiment, at least one of the identifier and digital watermark are changed each time the system justifies the personal certificate.

Fig. 1





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 5333

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 96 36163 A (RHOADS GEOFFREY B ;DIGIMARC CORP (US)) 14 November 1996 (1996-11-14) * page 67, line 29 - page 69, line 4 *	1-5, 7-12, 15-19	H04N1/32
Y	US 5 354 097 A (TEL TEUNIS) 11 October 1994 (1994-10-11) * column 5, line 1 - line 54; figure 2 *	1,8, 16-18	
Y	ZHAO J: "a www service to embed and prove digital copyright watermarks" PROCEEDINGS OF THE EUROPEAN CONFERENCE ON MULTIMEDIA APPLICATIONS, SERVICES AND TECHNIQUES - 31 December 1996 (1996-12-31) pages 695-709, XP000199921 * abstract * * Page 701, "Use of a Watermark Server" *	1,8, 16-18	
A	EP 0 581 317 A (INTERACTIVE HOME SYSTEMS) 2 February 1994 (1994-02-02)		TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	EP 0 859 503 A (NIPPON ELECTRIC CO) 19 August 1998 (1998-08-19)		H04N G07D
A	US 5 719 939 A (TEL TEUNIS) 17 February 1998 (1998-02-17)		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 16 January 2003	Examiner Hazel, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 503 03 12 (P04C2)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 5333

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-01-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9636163	A	14-11-1996	US 5832119 A	03-11-1998
			US 5748783 A	05-05-1998
			US 5841978 A	24-11-1998
			AT 230539 T	15-01-2003
			AT 216546 T	15-05-2002
			AU 6022396 A	29-11-1996
			CA 2218957 A1	14-11-1996
			DE 69620751 D1	23-05-2002
			DE 69620751 T2	31-10-2002
			EP 1003324 A2	24-05-2000
			EP 1049320 A1	02-11-2000
			EP 1137251 A2	26-09-2001
			EP 0824821 A2	25-02-1998
			JP 2002504272 T	05-02-2002
			WO 9636163 A2	14-11-1996
			US 2002164049 A1	07-11-2002
			US 6111954 A	29-08-2000
			US 6438231 B1	20-08-2002
			US 5862260 A	19-01-1999
			US 2001055407 A1	27-12-2001
			US 2001010730 A1	02-08-2001
			US 2001016051 A1	23-08-2001
			US 2002067844 A1	06-06-2002
			US 2002118831 A1	29-08-2002
			US 2002090112 A1	11-07-2002
			US 5841886 A	24-11-1998
			US 2002090114 A1	11-07-2002
			US 2002136430 A1	26-09-2002
			US 2002170966 A1	21-11-2002
			US 2002188841 A1	12-12-2002
			US 6324573 B1	27-11-2001
			US 6311214 B1	30-10-2001
			US 6408331 B1	18-06-2002
			US 6286036 B1	04-09-2001
			US 6411725 B1	25-06-2002
			US 6122403 A	19-09-2000
			US 2001032251 A1	18-10-2001
			US 2002016816 A1	07-02-2002
			US 2002029253 A1	07-03-2002
			US 2002078146 A1	20-06-2002
			US 2002009208 A1	24-01-2002
US 5354097	A	11-10-1994	NL 9001368 A	02-01-1992
			AT 122968 T	15-06-1995
			CA 2085113 A1	16-12-1991
			DE 69110044 D1	29-06-1995

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 5333

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

16-01-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5354097	A		DE 69110044 T2	09-11-1995
			DK 533829 T3	24-07-1995
			EP 0533829 A1	31-03-1993
			ES 2074277 T3	01-09-1995
			JP 2793366 B2	03-09-1998
			JP 6503762 T	28-04-1994
			WO 9119614 A1	26-12-1991
			US 5719939 A	17-02-1998
EP 0581317	A	02-02-1994	US 5721788 A	24-02-1998
			CA 2101673 A1	01-02-1994
			EP 0581317 A2	02-02-1994
			JP 6343128 A	13-12-1994
			US 5930377 A	27-07-1999
			US 2002181740 A1	05-12-2002
			US 6072888 A	06-06-2000
			US 2002037090 A1	28-03-2002
			US 6317505 B1	13-11-2001
			US 6137892 A	24-10-2000
			US 6307950 B1	23-10-2001
			US 2001002213 A1	31-05-2001
			US 6459803 B1	01-10-2002
			US 2002061119 A1	23-05-2002
			US 2002044673 A1	18-04-2002
			US 5809160 A	15-09-1998
EP 0859503	A	19-08-1998	JP 10224793 A	21-08-1998
			CA 2229395 A1	12-08-1998
			EP 0859503 A2	19-08-1998
			SG 86997 A1	19-03-2002
			US 2001040977 A1	15-11-2001
US 5719939	A	17-02-1998	NL 9001368 A	02-01-1992
			AT 122968 T	15-06-1995
			CA 2085113 A1	16-12-1991
			DE 69110044 D1	29-06-1995
			DE 69110044 T2	09-11-1995
			DK 533829 T3	24-07-1995
			EP 0533829 A1	31-03-1993
			ES 2074277 T3	01-09-1995
			JP 2793366 B2	03-09-1998
			JP 6503762 T	28-04-1994
			WO 9119614 A1	26-12-1991
			US 5354097 A	11-10-1994

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82